

Remote-Kamerasteuereinheit mit Touchscreen

AW-RP150

Einfache, gut sichtbare intuitive Kamerasteuerung



KEY FEATURES

- Großer Touchscreen für leichte Bedienbarkeit
- Neuer Joystick für einhändige Bedienung
- Vereinfachte Preset-/Tracing-Speicherfunktionen für die PTZ-Kamera
- Intuitive Designelemente basierend auf direkten Praxiserfahrungen in der Roboterkamerabedienung
- 3G-SDI Active Through Output, 5 x RS-422, LAN PoE+, 2 x GPIOs

Als neueste Remote-Kamerasteuereinheit bildet die AW-RP150 eine perfekte Ergänzung der professionellen PTZ-Kamerasysteme von Panasonic. Grundlegend funktionsgleich mit AW-RP120 und AW-RP50 weist sie jedoch erhebliche Verbesserungen gegenüber diesen Modellen auf, zum Beispiel den neuen mit einer Hand bedienbaren Joystick (zur PTZ- oder Fokussteuerung) und einen großen LCD-Touchscreen als Monitor und für Menüeinstellungen.

Ein Kipphebel am Joystick unterstützt die Schwenk-Neige-Funktion mit präziser Zoom- und Fokussteuerung für intuitive einhändige Bedienung. Das integrierte Touch-Display ermöglicht eine schnelle und einfache Bedienung aller wichtigen Kamerafunktionen.

SPECIFICATIONS

Power Requirements	12 V DC (10.8 V to 13.2 V)
Current Consumption	1.0 A (Connector Input) 0.6 A (PoE+ power supply)
Ambient Operating Temperature	0 °C to 40 °C (32 °F to 104 °F)
Ambient Operating Humidity	20% to 90% (no condensation)
Storage Temperature	-20 °C to 50 °C (-4 °F to 122 °F)
Gewicht	Approx. 3.2 kg (7.05 lb)
Dimensions (W x H x D) (mm)	342 mm x 178 mm x 245 mm(excluding protrusions)
Dimensions (W x H x D) (inch)	13-15/32 inches x 7 inches x 9-21/32 inches(excluding protrusions)
Controller Supported Equipment	IP/RS422 AW-UE150W/K, AW-HR140*1, AW-HE130W/K*1, AW-HN130W/K*1, AW-UE70W/K*1, AW-UN70W/K*1, AW-HE40 Series*1, AW-HN40HW/HK*1, AW-HE38HW/HK*1, AW-HN38HW/HK*1
Input	DC 12 V IN XLR 4-pin 3G-SDI IN SMPTE292 / 75 Ω (BNC x 1) Supported formats: 1080/59.94p*2, 1080/50p*2, 1080/59.94i, 1080/50i, 1080/23.98p, 1080/25p, 1080/23.98PsF, 1080/25PsF
Output	ACTIVE THRU OUT SMPTE292 / 75 Ω (BNC x 1)
Input/Output	IP CONT: ===== 100BASE-TX ----- PoE+ input ----- Connection cable: LAN cable, max. 100 m (328 ft) • When connecting the unit via a switching hub: Straight cable or a cross cable (category 5 cable), STP (Shielded Twisted Pair) cable recommended • When connecting the unit directly: Crossover cable (category 5 cable), STP (Shielded Twisted Pair) cable recommended ===== SERIAL CONT (RJ-45): ===== RS-422 (control signals for remote cameras), TALLY OUT ----- Connecting cable: Straight cable (category 5e or better shielded cable), max. 1000 m (3280 ft) ----- TALLY OUT: Open collector output (negative logic) Maximum voltage resistance DC 24 V, Maximum current 50 mA ===== TALLY/GPIO 1 ===== D-sub 25-pin, female, inch thread ----- TALLY IN : 10 inputs (for receiving photocoupler signals) ----- GPI : 6 inputs (for receiving photocoupler signals) GPIO : 5 inputs (for receiving photocoupler signals) or 5 outputs (open collector outputs, negative logic) • Input/output switched with menu settings ===== GPIO 2 ===== D-sub 25-pin, female, inch thread ----- GPI : 10 inputs (for receiving photocoupler signals) GPIO : 10 inputs (for receiving photocoupler signals) or 10 outputs (open collector outputs, negative logic) • Input/output switched with menu settings Reserve connectors: 2 connectors (For future expansion feature)

LCD Display	7-inch Touch Panel GUI Monitor (WVGA (800×480))
SD Memory Card Slot	SDHC / SDXC Memory Card Slot x 1
No. of Connectable Cameras	200 (IP), 5 (RS422)
No. of Camera Selection Buttons	10
No. of Camera Groups	20 (10 units per 1 group)
Preset Memory	No. of memory : presets 100
Tracing Memory	No. of cameras : Cam1 to Cam10 Recording time, no. of memory settings : Maximum 5 min. total per camera, maximum of 10 settings per camera
No. of User Assignable Buttons	6 + up to 10 on the LCD menu
Pan / Tilt Speed Adjustment	7 levels
Tally LED display color	green / red
Note	*1: Connection with the AW-RP150GJ is planned for future support. Contact your sales representative for further information on when support will be available for this feature. Use may require a software version update. *2: Level-A support only.
PoE+	IEEE802.3at standard: DC 42 V to 57 V (Camera Input)

URL: <https://business.panasonic.de/professional-kamera/Remote-Kamerasteuereinheit/AW-RP150>

CONTACT

Web: <https://business.panasonic.de/professional-kamera/contact-us>